

View Online at <https://aerobasegroup.com/nsn/6625-00-181-2436>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

1.765 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.375 inches

**Overall Height:**

3.328 inches

**Overall Width:**

3.546 inches

**Mounting Slot Width:**

0.125 inches

**Mounting Slot Length:**

0.125 inches

**Scale Division Quantity:**

50 single indicator 2nd range

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four slot rectangular/square open ends

**Sensitivity Rating:**

1.5 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.125 inches

**Meter Body Diameter Behind Mounting Flange:**

2.390 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 slotted hole

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

-15.0 to 1.0 decibels single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Mirror scale and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

On front, decibels; 1 mw 75

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0