

View Online at <https://aerobasegroup.com/nsn/6625-00-181-2436>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

1.765 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches

Overall Height:

3.328 inches

Overall Width:

3.546 inches

Mounting Slot Width:

0.125 inches

Mounting Slot Length:

0.125 inches

Scale Division Quantity:

50 single indicator 2nd range

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four slot rectangular/square open ends

Sensitivity Rating:

1.5 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.125 inches

Meter Body Diameter Behind Mounting Flange:

2.390 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 slotted hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-15.0 to 1.0 decibels single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Mirror scale and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

On front, decibels; 1 mw 75

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0