

View Online at <https://aerobasegroup.com/nsn/6625-00-187-1788>

Circuit Current For Which Designed:

Dc

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

30 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.063 inches

Meter Body Diameter Behind Mounting Flange:

2.675 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-150.0/+150.0 microamperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0