

View Online at <https://aerobasegroup.com/nsn/6625-00-187-4919>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.790 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.180 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.980 inches

Meter Body Diameter Behind Mounting Flange:

2.760 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-20.0 to 0.0 decibels single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Zero set to left of minus 20

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

100.0 megohms insulation resistance

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0