

View Online at <https://aerobasegroup.com/nsn/6625-00-192-0198>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.945 inches

Overall Height:

0.910 inches

Overall Width:

2.145 inches

Mounting Hole Diameter:

0.120 inches

Scale Division Quantity:

12 single indicator single range

Distance Between Mounting Facility Centers:

1.906 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Panel For Which Designed:

Nonmagnetic

Meter Depth Behind Mounting Flange:

2.343 inches

Meter Body Width Behind Mounting Flange:

1.710 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 2.4 milliamperes, ac single indicator single range

Meter Body Height Behind Mounting Flange:

0.610 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Markings:

Red band from 0.6 to 1.2

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0