## NSN 6625-00-192-7629

Ammeter - Page 1 of 2

Ac

Overall Length: 11.000 inches

3.375 inches

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-192-7629

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.373 IIICHES
Overall Height:
Between 4.250 inches and 4.750 inches
Overall Width:
Between 4.250 inches and 4.750 inches
Scale Division Quantity:
20 single indicator single range
Mounting Stud Length:
Between 0.500 inches and 0.750 inches
Environmental Protection:
Dustproof
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Frequency Response Range:
+59.100/+60.900 hertz
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
10.000 inches
Meter Body Diameter Behind Mounting Flange:
3.980 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

## NSN 6625-00-192-7629

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+2.0 kiloamperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Test Data Document:
81349-mil-m-16034/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A310a0