NSN 6625-00-192-7674

Ammeter - Page 1 of 2

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-192-7674

| 7.6 |
|---|
| Overall Length: |
| 4.360 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches |
| Overall Height: |
| 4.500 inches |
| Overall Width: |
| 4.500 inches |
| Scale Division Quantity: |
| 100 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Frequency Response Range: |
| +59.100/+60.900 hertz |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.5/+1.5 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 4.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.980 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |

NSN 6625-00-192-7674

Ammeter - Page 2 of 2



| Measurement Range: | |
|------------------------|----------------------------------|
| +0.0/+1500.0 amperes, | ac single indicator single range |
| Mounting Stud Diamet | er: |
| 0.250 inches | |
| Scale Selection Method | d: |
| Switch | |
| Features Provided: | |
| Magnetic shield | |
| Movement Suspension | Method: |
| Jewel pivot base | |
| Circuit Attachment Me | thod And Quantity: |
| 2 threaded stud | |
| Nuclear Hardness Criti | ical Feature: |
| Nonhardened | |
| Style Designator: | |
| Rectangular flush mtg | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A310a0 | |