NSN 6625-00-192-7679

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-192-7679

Circuit Current	For	Which	Designed:
-----------------	-----	-------	-----------

Ac

Overall Length:

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

Between 0.500 inches and 0.750 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+59.100/+60.900 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

10.000 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

NSN 6625-00-192-7679

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+400.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Switch
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Test Data Document:
31349-mil-m-16034/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Filg:
A310a0