## NSN 6625-00-192-7680

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-192-7680

## **Circuit Current For Which Designed:**

Ac

**Overall Length:** 

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

3.375 inches

**Overall Height:** 

Between 4.250 inches and 4.750 inches

**Overall Width:** 

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

50 single indicator single range

**Mounting Stud Length:** 

Between 0.500 inches and 0.750 inches

**Indicator Type:** 

Dial w/pointer

**Installation Design:** 

Panel

**Mounting Arrangement Style:** 

Four hole/stud rectangular/square

Frequency Response Range:

+59.100/+60.900 hertz

**Dial Scale Marking Color:** 

Black single indicator single range

**Accuracy In Percent:** 

-1.5/+1.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:** 

10.000 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

**Movement Type:** 

Moving iron vane

**Background Color:** 

White single indicator single range

**Pointer Color:** 

Black single indicator single range

**Power Source:** 

External

**Mounting Facility Type And Quantity:** 

4 threaded stud

## NSN 6625-00-192-7680

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+5.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Features Provided:
Magnetic shield
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic and steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Test Data Document:
81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A310a0