NSN 6625-00-192-8079

Voltmeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-192-8079

| Overall Length: |
|---|
| 3.250 inches |
| Overall Height: |
| 5.250 inches |
| Overall Width: |
| 5.000 inches |
| Scale Division Quantity: |
| 25 single indicator all ranges |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Rack |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -0.5/+0.5 at full scale single indicator all ranges |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| +0.0 to 300.0 volts, dc single indicator 2nd range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 3 binding post |
| Material: |
| Plastic and steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |

NSN 6625-00-192-8079

Voltmeter - Page 2 of 2



| Style | Desia | nator: |
|-------|-------|--------|
| | | |

Rectangular or square

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Departure From Cited Designator:

As modified by measurement range per indicator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0