NSN 6625-00-195-5393

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-195-5393

| Circuit Current For Which Designed: |
|---|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 5000.0 |
| Overall Length: |
| 3.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.844 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.476 inches |
| Overall Height: |
| 0.900 inches |
| Overall Width: |
| 2.250 inches |
| Mounting Hole Diameter: |
| 0.118 inches |
| Scale Division Quantity: |
| 20 single indicator single range |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.200 inches |
| Meter Body Width Behind Mounting Flange: |
| 2.250 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Measurement Range: |
| +0.0/+100.0 microamperes, dc single indicator single range |
| Meter Body Height Behind Mounting Flange: |
| 0.900 inches |
| Features Provided: |

Magnetic shield

NSN 6625-00-195-5393

Ammeter - Page 2 of 2



Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Style Designator: Rectangular flush mtg Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A310a0