Ammeter - Page 1 of 3

Dc



View Online at https://aerobasegroup.com/nsn/6625-00-196-8775

Circuit Current For Which Designed: Dielectric Withstanding Voltage In Volts: 2600.0 **Overall Length:** 11.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.376 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 3.376 inches **Overall Height:** Between 4.250 inches and 4.750 inches **Overall Width:** Between 4.250 inches and 4.750 inches **Scale Division Quantity:** 30 single indicator single range **Mounting Stud Length:** 0.625 inches **Environmental Protection:** Dust resistant and humidity resistant and shock resistant and vibration resistant **Furnished Items And Quantity:** Mtg hdw 4; term. Hdw 2 Indicator Type: Dial w/pointer Installation Design: Panel **Mounting Arrangement Style:** Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts **Dial Scale Marking Color:** Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range **Unable To Decode:** Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 9.000 inches Meter Body Diameter Behind Mounting Flange: 3.960 inches Movement Type: Moving coil, permanent magnet

NSN 6625-00-196-8775

Ammeter - Page 2 of 3



Background Color: White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External **Mounting Facility Type And Quantity:** 4 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+300.0 amperes, dc single indicator single range **Mounting Stud Diameter:** 0.250 inches **Scale Selection Method:** Terminal **Features Provided:** Electrical overload protection and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized Material: Plastic or stainless steel **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg **Supplementary Features: Resists friction effects Test Data Document:** 81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-16034/2 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

NSN 6625-00-196-8775

Ammeter - Page 3 of 3

Demilitarization:

No

Fiig:

A310a0

