## NSN 6625-00-196-8779

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-196-8779

**Circuit Current For Which Designed:** 

Dc

**Dielectric Withstanding Voltage In Volts:** 

1500.0

**Overall Length:** 

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

Between 3.346 inches and 3.406 inches

**Overall Height:** 

Between 4.250 inches and 4.750 inches

**Overall Width:** 

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

40 single indicator single range

**Mounting Stud Length:** 

Between 0.500 inches and 0.750 inches

**Environmental Protection:** 

Cold resistant and dust resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:** 

Nut 12; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

**Mounting Arrangement Style:** 

Four hole/stud rectangular/square

**Dial Scale Marking Color:** 

Black single indicator single range

**Accuracy In Percent:** 

-1.5/+1.5 at full scale single indicator single range

**Unable To Decode:** 

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:** 

9.000 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

**Background Color:** 

White single indicator single range

**Pointer Color:** 

Black single indicator single range

## NSN 6625-00-196-8779

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:	
4 threaded stud	
Scale Graduation Type:	
Linear single indicator single range	
Measurement Range:	
+0.0/+2.0 kiloamperes, dc single indicator single range	
Mounting Stud Diameter:	
0.250 inches	
Features Provided:	
Electrical overload protection and external shunting and magnetic shield and zero adjuster	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Special Features:	
Ruggedized	
Material:	
Plastic or stainless steel	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Paint	
Style Designator:	
Rectangular flush mtg	
Supplementary Features:	
Friction effect res	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A310a0	