## NSN 6625-00-196-8794

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-196-8794

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2600.0
Overall Depth:
3.375 inches
Overall Length:
6.000 inches
Overall Width:
5.750 inches
Scale Division Quantity:
120 single indicator single range
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Case 1
Indicator Type:
Dial w/pointer
Installation Design:
Bench
Frequency Response Range:
+25.000 to 125.000 hertz
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-0.75 to 0.75 at full scale single indicator single range
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0 to 600.0 volts, ac single indicator single range
Scale Selection Method:

Mirror scale and zero adjuster

**Features Provided:** 

Terminal

## **NSN 6625-00-196-8794** Voltmeter - Page 2 of 2



Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 binding post  Special Features:  Ruggedized  Material:  Plastic  Nuclear Hardness Critical Feature:  Nonhardened  Surface Treatment:  Paint  Style Designator:
Circuit Attachment Method And Quantity:  2 binding post  Special Features: Ruggedized  Material: Plastic  Nuclear Hardness Critical Feature: Nonhardened  Surface Treatment: Paint
2 binding post  Special Features: Ruggedized  Material: Plastic  Nuclear Hardness Critical Feature: Nonhardened  Surface Treatment: Paint
Special Features: Ruggedized  Material: Plastic  Nuclear Hardness Critical Feature: Nonhardened  Surface Treatment: Paint
Ruggedized  Material:  Plastic  Nuclear Hardness Critical Feature:  Nonhardened  Surface Treatment:  Paint
Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint
Plastic  Nuclear Hardness Critical Feature:  Nonhardened  Surface Treatment:  Paint
Nuclear Hardness Critical Feature:  Nonhardened  Surface Treatment:  Paint
Nonhardened Surface Treatment: Paint
Surface Treatment:
Paint
Style Designator:
Portable
Test Data Document:
31349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-m-16034/13 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A310a0