

View Online at <https://aerobasegroup.com/nsn/6625-00-196-8794>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Depth:

3.375 inches

Overall Length:

6.000 inches

Overall Width:

5.750 inches

Scale Division Quantity:

120 single indicator single range

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Case 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Frequency Response Range:

+25.000 to 125.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.75 to 0.75 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 600.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Mirror scale and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Portable

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-16034/13 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0