

View Online at <https://aerobasegroup.com/nsn/6625-00-197-2365>

**Reliability Indicator:**

Not established

**Mounting Provision Quantity:**

2

**Overall Length:**

Between 1.970 inches and 2.030 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.845 inches and 0.905 inches

**Overall Height:**

Between 1.658 inches and 1.708 inches

**Overall Width:**

Between 1.220 inches and 1.280 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.190 inches and 0.220 inches

**Furnished Items And Quantity:**

Nut 4; screw 2; lockwasher 4

**Usage Design:**

External

**Accuracy In Percent:**

-0.25/+0.25 all ranges

**Element Material:**

Copper alloy

**Mounting Method:**

Unthreaded hole

**Cubic Measure:**

4.438 cubic inches

**Terminal Location:**

Both sides and top

**Voltage Drop In Millivolts:**

50.0

**Current Rating And Type:**

80.0 amperes dc

**Test Data Document:**

58536-a-a-55524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 screw and 2 threaded stud

**Specification Data:**

58536-a-a-55524/1 government specification

**Specification Or Standard:**

Mmsa800 type and ms91586-4 part

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A33500