

View Online at <https://aerobasegroup.com/nsn/6625-00-197-2365>

Reliability Indicator:

Not established

Mounting Provision Quantity:

2

Overall Length:

Between 1.970 inches and 2.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.845 inches and 0.905 inches

Overall Height:

Between 1.658 inches and 1.708 inches

Overall Width:

Between 1.220 inches and 1.280 inches

Unthreaded Mounting Hole Diameter:

Between 0.190 inches and 0.220 inches

Furnished Items And Quantity:

Nut 4; screw 2; lockwasher 4

Usage Design:

External

Accuracy In Percent:

-0.25/+0.25 all ranges

Element Material:

Copper alloy

Mounting Method:

Unthreaded hole

Cubic Measure:

4.438 cubic inches

Terminal Location:

Both sides and top

Voltage Drop In Millivolts:

50.0

Current Rating And Type:

80.0 amperes dc

Test Data Document:

58536-a-a-55524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 screw and 2 threaded stud

Specification Data:

58536-a-a-55524/1 government specification

Specification Or Standard:

Mmsa800 type and ms91586-4 part

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A33500