

View Online at <https://aerobasegroup.com/nsn/6625-00-197-3034>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.430 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches

Overall Height:

4.000 inches

Overall Width:

4.680 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.650 inches

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.080 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+0.0/+30.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0