

View Online at <https://aerobasegroup.com/nsn/6625-00-198-9950>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

1.110 inches

Overall Height:

0.687 inches

Overall Width:

0.687 inches

Environmental Protection:

Dust resistant and fire resistant and fungus resistant and heat resistant and salt water resistant and shock resistant and water resistant

Furnished Items And Quantity:

Mtg hdw 2, one neoprene rubber washer, one nut

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.822 inches

Meter Body Diameter Behind Mounting Flange:

0.595 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

One black line at 0 milliamperes, one black line at 1 milliampere and one red line at .3 milliamperes deflection points

Mounting Facility Type And Quantity:

1 collar and 1 threaded body

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Features:

Ruggedized

Special Markings:

Red term. Is pos

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Zero adjust is on back of meter

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0