## NSN 6625-00-199-7628

Multiple Scale Meter - Page 1 of 2

**Circuit Current For Which Designed:** 

Dc



View Online at https://aerobasegroup.com/nsn/6625-00-199-7628

Overall Length:
2.125 inches
Overall Height:
3.500 inches
Overall Width:
3.500 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Red single indicator 1st range
Accuracy In Percent:
-3.0 to 3.0 at full scale single indicator all ranges
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Deinter Celer
Pointer Color:
Red single indicator all ranges
Red single indicator all ranges
Red single indicator all ranges  Power Source:
Red single indicator all ranges  Power Source:  External
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 threaded stud
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 threaded stud  Special Features:
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range:  -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 threaded stud  Special Features:  2250 ohms res
Red single indicator all ranges  Power Source:  External  Scale Graduation Type:  Nonlinear single indicator all ranges  Measurement Range: -6.0 to 10.0 decibels single indicator 1st range  Features Provided:  Knife edge pointer  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity: 2 threaded stud  Special Features: 2250 ohms res  Special Markings:

## NSN 6625-00-199-7628

Multiple Scale Meter - Page 2 of 2



Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular surface mtg
Supplementary Features:
thm:mounting
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0