## NSN 6625-00-200-2644

Ammeter - Page 1 of 2

1500.0

Overall Length: 3.688 inches Overall Height: 1.630 inches Overall Width:

**Circuit Current For Which Designed:** 

**Dielectric Withstanding Voltage In Volts:** 



View Online at https://aerobasegroup.com/nsn/6625-00-200-2644

3.797 inches
Distance Between Mounting Facility Centers:
3.750 inches
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
3.172 inches
Meter Body Width Behind Mounting Flange:
3.330 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
White single indicator single range  Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 snap slide
Mounting Facility Type And Quantity: 2 snap slide Measurement Range:
Mounting Facility Type And Quantity: 2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range
Mounting Facility Type And Quantity: 2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange:
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange:  0.875 inches
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange:  0.875 inches  Features Provided:
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange: 0.875 inches  Features Provided: Portable
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange:  0.875 inches  Features Provided: Portable  Movement Suspension Method:
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange: 0.875 inches  Features Provided: Portable  Movement Suspension Method: Jewel pivot base
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange: 0.875 inches  Features Provided: Portable  Movement Suspension Method: Jewel pivot base  Circuit Attachment Method And Quantity:
Mounting Facility Type And Quantity:  2 snap slide  Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range  Meter Body Height Behind Mounting Flange: 0.875 inches  Features Provided: Portable  Movement Suspension Method: Jewel pivot base  Circuit Attachment Method And Quantity: 2 threaded stud

## NSN 6625-00-200-2644

Ammeter - Page 2 of 2



Desig	

Rectangular flush mtg

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0