

View Online at <https://aerobasegroup.com/nsn/6625-00-204-5951>

Circuit Current For Which Designed:

Dc

Overall Length:

1.420 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Scale Division Quantity:

2 single indicator 2nd range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.5 to 1.5 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.060 inches

Meter Body Diameter Behind Mounting Flange:

2.690 inches

Movement Type:

Electrodynamometer

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator 3rd range

Measurement Range:

+90.0 to 100.0 percent modulation single indicator 2nd range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

234.0 ohms resistance

Special Markings:

Power watts at watts scale

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Tested iaw mil-std-810

Style Designator:

Rectangular flush mtg

Supplementary Features:

Electromagnetic

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0