NSN 6625-00-205-2769

Voltmeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-205-2769

| Dc |
|---|
| Overall Length: |
| 1.285 inches |
| Overall Height: |
| 1.640 inches |
| Overall Width: |
| 1.980 inches |
| Scale Division Quantity: |
| 30 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Environmental Protection: |
| Dustproof |
| Distance Between Mounting Facility Centers: |
| 1.250 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Two hole/stud |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 0.820 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.250 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |

NSN 6625-00-205-2769

Voltmeter - Page 2 of 2



| Measurement Range: |
|--|
| +0.0 to 30.0 volts, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.112 inches |
| Scale Selection Method: |
| Switch |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |