

View Online at <https://aerobasegroup.com/nsn/6625-00-212-3185>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

11.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

4.500 inches

**Overall Width:**

4.500 inches

**Scale Division Quantity:**

80 single indicator single range

**Mounting Stud Length:**

Between 0.500 inches and 0.750 inches

**Furnished Items And Quantity:**

Lock washers 4; hex nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5/+1.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

10.000 inches

**Meter Body Diameter Behind Mounting Flange:**

3.980 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-80.0/+80.0 amperes, dc single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

Magnetic shield

**Criticality Code Justification:**

Feat

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo1106

**Material:**

Plastic or steel

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0