

View Online at <https://aerobasegroup.com/nsn/6625-00-213-8601>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.690 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

76 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

**Mounting Bolt Circle Diameter:**

Between 2.430 inches and 2.450 inches

**Furnished Items And Quantity:**

Nut 4; washer 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

500.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.650 inches

**Meter Body Diameter Behind Mounting Flange:**

2.200 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Ft/min; retr; ext; 400, 200, 0, 200, 400, 600, 800, 1000, 1200, 1400

**Mounting Facility Type And Quantity:**

1 flange and 3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Luminous scale marking and magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

Conforms to mil-m-10304/4

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Mechanical and electrical zero are at three o'clock position; place divider line on scale between center and zero

**Fsc Application Data:**

Electrical, electronic properties measuring and test instruments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0