NSN 6625-00-214-1807

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-214-1807

Overall Length:
13.500 inches
Overall Height:
7.500 inches
Overall Width:
9.750 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 60.0 hertz
Accessory Components And Quantity:
Set instructions 1; set leads, test 1
Voltage Rating:
Between 105.0 volts and 125.0 volts
Beam Quantity:
1
Mounting Method:
Portable case
Screen Size:
3.000 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Frequency Range:
+15.000/+30000.000 hertz
Trigger Sweep Polarity Switch:
Included
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
30.0 millivolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:
600.0 millivolts any acceptable outside diameter
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
85.0 millivolts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Ratings
1.7 volts rms per inch

NSN 6625-00-214-1807

Oscilloscope - Page 2 of 2



Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 0.0 kilohertz and 500.0 kilohertz
Y-axis Frequency Response Rating:
Between 0.0 kilohertz and 500.0 kilohertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
Yes - demil/mli
Fiig:
Г320-g