## NSN 6625-00-214-4018

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-214-4018

### Circuit Current For Which Designed:

Ac

#### **Dielectric Withstanding Voltage In Volts:**

3000.0

#### **Overall Length:**

2.470 inches

#### Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

#### **Overall Diameter:**

2.695 inches

#### Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

#### Mounting Bolt Circle Diameter:

2.440 inches

#### Furnished Items And Quantity:

#### Nuy 5; washer 5

Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Three hole/stud bolt circle

#### Sensitivity Rating:

5.0 volts

#### Dial Scale Marking Color:

Black single indicator single range

#### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

#### Meter Depth Behind Mounting Flange:

1.430 inches

#### Meter Body Diameter Behind Mounting Flange:

2.150 inches

#### Movement Type:

Moving iron vane

#### **Background Color:**

White single indicator single range

#### **Pointer Color:**

Black single indicator single range

#### **Power Source:**

External

#### Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

# NSN 6625-00-214-4018

Ammeter - Page 2 of 2



	cale Graduation Type: onlinear single indicator single range
	leasurement Range:
	0.0/+40.0 amperes, ac single indicator single range
	eatures Provided:
	uminous scale marking and magnetic shield and zero adjuster
	lovement Suspension Method:
	aut band
	ircuit Attachment Method And Quantity:
	threaded stud
_	pecial Features:
	uggedized
	pecial Markings:
	ealed do not open on back of meter; plus sign under positive terminal
	laterial:
S	tainless steel
s	urface Treatment:
E	namel semigloss
S	pecial Test Features:
С	onforms to mil-m-10304/4
S	tyle Designator:
R	ound flush mtg
F	sc Application Data:
Т	est set, elect. Equip.
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
Y	es - demil/mli
Fi	iig:
A	310a0