

View Online at <https://aerobasegroup.com/nsn/6625-00-215-9537>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

3.780 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.718 inches

**Overall Height:**

1.000 inches

**Overall Width:**

2.688 inches

**Mounting Hole Diameter:**

0.140 inches

**Scale Division Quantity:**

20 single indicator single range

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

50.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.500 inches

**Meter Body Width Behind Mounting Flange:**

2.100 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

M 5; 0; 5

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.000 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Resistance 500 ohms

**Style Designator:**

Rectangular semi-flush mtg

**Fsc Application Data:**

Test set, electronic systems, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0