

View Online at <https://aerobasegroup.com/nsn/6625-00-222-7572>

Circuit Current For Which Designed:

Dc

Overall Length:

1.970 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.310 inches

Overall Height:

1.770 inches

Overall Width:

2.260 inches

Scale Division Quantity:

48 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Terminal hardware 2; mounting hardware 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.300 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 120.0 decibels single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Extended mark at 0; 20; 40; 60; 80; 100; 120; db above threshold

Material:

Plastic polycarbonate

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0