

View Online at <https://aerobasegroup.com/nsn/6625-00-223-1944>

Circuit Current For Which Designed:

Dc

Overall Length:

1.925 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

100 single indicator single range

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.550 inches

Meter Body Diameter Behind Mounting Flange:

2.150 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Null; m 1; m .8; m .6; m .4; m .2; 0; .2; .4; .6; .8; 1

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0