## NSN 6625-00-223-1944

Null Meter - Page 1 of 2

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-223-1944

Dc
Overall Length:
1.925 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
100 single indicator single range
Overall Diameter:
2.695 inches
Mounting Bolt Circle Diameter:
2.440 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0 to 1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.550 inches
Meter Body Diameter Behind Mounting Flange:
2.150 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:
Null; m 1; m .8; m .6; m .4; m .2; 0; .2; .4; .6; .8; 1

Linear single indicator single range Features Provided:

**Scale Graduation Type:** 

3 unthreaded hole

**Mounting Facility Type And Quantity:** 

Zero adjuster

## NSN 6625-00-223-1944

Null Meter - Page 2 of 2



Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0