

View Online at <https://aerobasegroup.com/nsn/6625-00-223-5740>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.390 inches

**Mounting Stud Length:**

Between 0.375 inches and 0.625 inches

**Overall Diameter:**

3.510 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+0.000025/+30.000000 megahertz

**Sensitivity Rating:**

800.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.010 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

3 threaded stud

**Measurement Range:**

+0.0/+500.0 milliamperes, rf single indicator single range

**Mounting Stud Diameter:**

Between 0.143 inches and 0.157 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 binding post

**Material:**

Plastic

**Style Designator:**

Round flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0