

View Online at <https://aerobasegroup.com/nsn/6625-00-223-5740>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.390 inches

Mounting Stud Length:

Between 0.375 inches and 0.625 inches

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.000025/+30.000000 megahertz

Sensitivity Rating:

800.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.010 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 threaded stud

Measurement Range:

+0.0/+500.0 milliamperes, rf single indicator single range

Mounting Stud Diameter:

Between 0.143 inches and 0.157 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Material:

Plastic

Style Designator:

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0