

View Online at <https://aerobasegroup.com/nsn/6625-00-223-9762>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

3.050 inches

Scale Division Quantity:

100 single indicator all ranges

Mounting Stud Length:

0.500 inches

Overall Diameter:

4.600 inches

Mounting Bolt Circle Diameter:

4.126 inches

Furnished Items And Quantity:

Mtg hdw 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.750 inches

Meter Body Diameter Behind Mounting Flange:

3.760 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

6 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-5.0/+5.0 amperes, dc single indicator 3rd range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

11 pin

Special Features:

Ruggedized

Special Markings:

Current dc

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0