

View Online at <https://aerobasegroup.com/nsn/6625-00-224-2404>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

2.330 inches

**Mounting Hole Diameter:**

0.156 inches

**Frequency Rating:**

400.0 hertz

**Overall Diameter:**

3.502 inches

**Mounting Bolt Circle Diameter:**

3.250 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

2.000 inches

**Meter Body Diameter Behind Mounting Flange:**

2.500 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

+0.0 to 5.0 watts single indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Self-illumination facility and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud and 2 wire lead

**Phase:**

Single

**Special Features:**

Wire leads for illumination facility to be 7 in. Long min

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0