NSN 6625-00-227-1008

Arbitrary Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

3000.0

Overall Length:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-227-1008

| 1.251 inches |
|---------------------------------------------------------|
| Scale Division Quantity: |
| 10 single indicator single range |
| Overall Diameter: |
| 1.250 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 0.901 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.187 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Scale Marking: |
| P min |
| Mounting Facility Type And Quantity: |
| 1 ring and 1 threaded body |
| Scale Graduation Type: |
| Linear single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Special Features: |
| Ruggedized |
| |

NSN 6625-00-227-1008

Arbitrary Scale Meter - Page 2 of 2



| Special Markings: |
|------------------------------------|
| ^o min |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel lusterless |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Гest set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |