

View Online at <https://aerobasegroup.com/nsn/6625-00-228-1968>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

5000.0

Overall Length:

2.395 inches

Scale Division Quantity:

2 single indicator single range

Overall Diameter:

2.201 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Pad 2; nut 4; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

10.0 amperes

Dial Scale Marking Color:

Green and red and white single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.239 inches

Meter Body Diameter Behind Mounting Flange:

2.036 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

-; +; amperes

Mounting Facility Type And Quantity:

1 bracket

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Knife edge pointer

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

On front, red band on left side; green band on right side of center

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0