## NSN 6625-00-229-0683

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-229-0683

## **Circuit Current For Which Designed:** Dc **Dielectric Withstanding Voltage In Volts:** 3000.0 **Overall Length:** 3.000 inches **Scale Division Quantity:** 100 single indicator single range Mounting Stud Length: 0.750 inches **Overall Diameter:** 2.700 inches Mounting Bolt Circle Diameter: 2.440 inches **Furnished Items And Quantity:** Mtg hdw 3; term. Hdw 2 **Indicator Type:** Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Unable To Decode: Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.650 inches Meter Body Diameter Behind Mounting Flange: 2.070 inches Movement Type: Moving coil, permanent magnet **Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:**

External

**Mounting Facility Type And Quantity:** 

3 threaded stud

## NSN 6625-00-229-0683

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+10.0 milliamperes, dc single indicator single range
Mounting Stud Diameter:
0.112 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Anodize and cadmium
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0