

View Online at <https://aerobasegroup.com/nsn/6625-00-229-7058>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.400 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

22 single indicator single range

Overall Diameter:

2.290 inches

Distance Between Mounting Facility Centers:

1.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.312 inches

Meter Body Diameter Behind Mounting Flange:

2.184 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Feet; m 100; 50; 200; 350; 500; 650; 800; 950; 1100; 1250; 1400; - f.S at left side of scale; + f.S at right side of scale; 0 w/arrow to right and left at center scale

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0