

View Online at <https://aerobasegroup.com/nsn/6625-00-229-7058>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.400 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

22 single indicator single range

**Overall Diameter:**

2.290 inches

**Distance Between Mounting Facility Centers:**

1.500 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.312 inches

**Meter Body Diameter Behind Mounting Flange:**

2.184 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Feet; m 100; 50; 200; 350; 500; 650; 800; 950; 1100; 1250; 1400; - f.S at left side of scale; + f.S at right side of scale; 0 w/arrow to right and left at center scale

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0