

View Online at <https://aerobasegroup.com/nsn/6625-00-232-0932>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.312 inches

Overall Height:

0.500 inches

Overall Width:

1.906 inches

Mounting Hole Diameter:

0.143 inches

Scale Division Quantity:

10 single indicator single range

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

1.718 inches

Furnished Items And Quantity:

Nut 2; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

No scale reading but level on top and phase on center of bottom

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Knife edge pointer

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Features:

Ruggedized

Special Markings:

Red band below phase marks

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0