

View Online at <https://aerobasegroup.com/nsn/6625-00-232-1111>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.000 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

3 single indicator single range

**Overall Diameter:**

3.500 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Nuts 4, washers 4, solder lugs 4

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+0.025/+35.000 kilohertz

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Measurement Range:**

+0.0/+3.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Movement Suspension Method:**

Metal pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Style Designator:**

Round flush mtg

**Test Data Document:**

81349-mil10304a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0