

View Online at <https://aerobasegroup.com/nsn/6625-00-232-8469>

Circuit Current For Which Designed:

Dc

Overall Length:

2.725 inches

Overall Height:

3.000 inches

Overall Width:

5.050 inches

Scale Division Quantity:

40 single indicator 2nd range

Barrel Width:

3.000 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.690 inches

Meter Body Width Behind Mounting Flange:

3.000 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

1 flange

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

-20.0 to 2.0 decibels above or below one milliwatt single indicator 1st range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

3.000 inches

Meter Barrel Depth:

1.380 inches

Features Provided:

Knife edge pointer and luminous scale marking and mirror scale and self-illumination facility and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Cal in blue at 0 of both scales

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0