NSN 6625-00-233-4172

Voltmeter - Page 1 of 2

Dc

Overall Length: 2.850 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-233-4172

Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
60 single indicator all ranges
Overall Diameter:
3.510 inches
Environmental Protection:
Shock resistant and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External

NSN 6625-00-233-4172

Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0 to 300.0 volts, dc single indicator 2nd range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A310a0