## NSN 6625-00-234-1476

Ammeter - Page 1 of 2

External



View Online at https://aerobasegroup.com/nsn/6625-00-234-1476

| Circuit Current For Which Designed:                                       |
|---|
| Dc  |
| Dielectric Withstanding Voltage In Volts:                                 |
| 1500.0  |
| Overall Length:   |
| 1.437 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.312 inches  |
| Overall Height:   |
| 1.758 inches  |
| Overall Width:  |
| 1.758 inches  |
| Mounting Hole Diameter:   |
| 0.223 inches  |
| Scale Division Quantity:  |
| 6 single indicator single range   |
| Environmental Protection:   |
| Dust resistant  |
| Indicator Type:   |
| Dial w/pointer  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:   |
| Four hole/stud rectangular/square   |
| Dial Scale Marking Color:   |
| Black single indicator single range                                       |
| Accuracy In Percent:  |
| -3.0/+3.0 at full scale single indicator single range                     |
| Meter Depth Behind Mounting Flange:                                       |
| 0.853 inches  |
| Meter Body Diameter Behind Mounting Flange:                               |
| 1.510 inches  |
| Movement Type:  |
| Moving coil, permanent magnet   |
| Background Color:   |
| White single indicator single range                                       |
| Pointer Color:  |
| Black single indicator single range                                       |
| Power Source:   |

## NSN 6625-00-234-1476

Ammeter - Page 2 of 2



| Mounting Facility Type And Quantity:                       |
|--|
| 4 unthreaded hole  |
| Scale Graduation Type:                                     |
| Linear single indicator single range                       |
| Measurement Range:   |
| +0.0/+500.0 milliamperes, dc single indicator single range |
| Scale Selection Method:                                    |
| Terminal   |
| Movement Suspension Method:                                |
| Jewel pivot base   |
| Circuit Attachment Method And Quantity:                    |
| 2 solder stud  |
| Material:  |
| Steel  |
| Nuclear Hardness Critical Feature:                         |
| Nonhardened  |
| Surface Treatment:   |
| Paint lusterless   |
| Style Designator:  |
| Rectangular flush mtg                                      |
| Fsc Application Data:                                      |
| Test set, electronic equipment                             |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A310a0   |
|  |