

View Online at <https://aerobasegroup.com/nsn/6625-00-234-5899>

Circuit Current For Which Designed:

Ac

Overall Length:

2.501 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

30 single indicator single range

Frequency Rating:

60.0 hertz

Overall Diameter:

2.297 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+25.000/+500.000 hertz

Sensitivity Rating:

72.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.5/+2.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.876 inches and 2.438 inches

Meter Body Diameter Behind Mounting Flange:

2.062 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+3.0 amperes, ac single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Features:

Meter to withstand 8 amps for 1 sec decreasing to 3 amps in 5 sec

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0