

View Online at <https://aerobasegroup.com/nsn/6625-00-237-3546>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.310 inches

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

Between 1.653 inches and 1.683 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Frequency Response Range:**

+25.000 to 125.000 hertz

**Sensitivity Rating:**

10000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.765 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 1.485 inches and 1.500 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 threaded body

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 10.0 volts, ac single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Anodize

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0