

View Online at <https://aerobasegroup.com/nsn/6625-00-237-4854>

Circuit Current For Which Designed:

Dc

Overall Length:

3.469 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.562 inches

Overall Width:

4.562 inches

Scale Division Quantity:

20 single indicator all ranges

Mounting Stud Length:

1.500 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Resonant Reed Quantity:

21

Meter Depth Behind Mounting Flange:

2.531 inches

Meter Body Diameter Behind Mounting Flange:

3.687 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+122.5 to 127.5 hertz single indicator 2nd range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A310a0