

View Online at <https://aerobasegroup.com/nsn/6625-00-237-8457>

**Circuit Current For Which Designed:**

Dc

**Reliability Indicator:**

Not established

**Overall Length:**

3.500 inches

**Overall Height:**

1.000 inches

**Overall Width:**

3.250 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

0.500 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

2.937 inches

**Barrel Width:**

1.687 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.188 inches

**Meter Body Width Behind Mounting Flange:**

2.625 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-200.0/+200.0 microamperes, dc single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Meter Body Height Behind Mounting Flange:**

1.219 inches

**Meter Barrel Depth:**

1.780 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic acrylic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg barrel, down

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0