

View Online at <https://aerobasegroup.com/nsn/6625-00-237-8482>

Circuit Current For Which Designed:

Dc

Overall Length:

2.170 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.231 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.992 inches

Overall Height:

4.206 inches

Overall Width:

5.483 inches

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.032 inches

Meter Body Diameter Behind Mounting Flange:

2.636 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-8.0 to 3.0 decibels above or below one milliwatt single indicator 1st range

Mounting Stud Diameter:

0.135 inches

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0